


Unsplit long arm



Split long arm

Range: 3300 Kg - 5000 Kg

- Rotating paper roll clamp for safe and effective vertical and horizontal roll handling.
- Slim and smooth arm and frame design, optimal visibility and advanced hydraulic operation.
- Pivoting arm movement. Short and long arms. Non-split long arm for single roll handling. Split arm for 1 - 2 roll handling.
- 180-degree rotation. Hydraulic cushioning in the vertical end positions.
- All hydraulic functions protected with built-in pressure relief valves and check valves. All service and maintenance points easily available.

Model	Capacity	Load Centre	Roll Range	Height	Weight	Horizontal Centre of Gravity	Vertical Centre of Gravity	Effective Thickness	Contact Pads	Contact Pad Gap	Mounting Height	Mounting Class
	Q kg	BP mm	A mm	D mm	W Kg	HCG mm	VCG mm	LL mm	M x N mm	O mm	H mm	ISO 2328
Single roll clamps - Unsplit long arm												
AR-45RH-13	5000	650	250-1300	1240	1175	290	395	212	280x500	200	220	3 / 4 A
AR-45RH-14	4800	700	250-1400	1240	1200	300	395	212	280x500	200	220	3 / 4 A
AR-45RH-15	4600	760	250-1520	1240	1230	315	395	212	280x500	200	220	3 / 4 A
AR-45RH-16	4500	800	250-1600	1240	1270	325	395	212	280x500	200	220	3 / 4 A
AR-45RH-17	4200	850	300-1700	1240	1305	340	395	212	280x500	200	220	3 / 4 A
AR-45RH-18	3900	915	350-1830	1240	1340	360	395	212	280x500	200	220	3 / 4 A
AR-45RH-19	3600	950	450-1900	1240	1380	370	395	212	280x500	200	220	3 / 4 A
AR-45RH-20	3500	1000	450-2000	1240	1410	390	395	212	280x500	200	220	3 / 4 A
AR-45RH-21	3300	1050	450-2100	1240	1440	400	395	212	280x500	200	220	3 / 4 A
1 - 2 roll clamps - Split long arm												
AR-45RJ-13	5000	650	250-1300	1240	1160	280	395	212	280x500	200	220	3 / 4 A
AR-45RJ-14	4800	700	250-1400	1240	1190	290	395	212	280x500	200	220	3 / 4 A
AR-45RJ-15	4600	760	250-1520	1240	1220	305	395	212	280x500	200	220	3 / 4 A
AR-45RJ-16	4500	800	250-1600	1240	1260	315	395	212	280x500	200	220	3 / 4 A
AR-45RJ-17	4200	850	300-1700	1240	1295	330	395	212	280x500	200	220	3 / 4 A
AR-45RJ-18	3900	915	350-1830	1240	1330	350	395	212	280x500	200	220	3 / 4 A
AR-45RJ-19	3600	950	450-1900	1240	1370	360	395	212	280x500	200	220	3 / 4 A
AR-45RJ-20	3500	1000	450-2000	1240	1400	380	395	212	280x500	200	220	3 / 4 A
AR-45RJ-21	3300	1050	450-2100	1240	1430	390	395	212	280x500	200	220	3 / 4 A

Notes:

- Two hydraulic functions required.
- Standard contact pads: cast pad with high-friction surface.
- Minimum 5-degree forward tilt on lift mast is required for horizontal handling.
- For 0-degree tilt, special arms are available. Consult Bolzoni.

Options:

- Special roll ranges.
- Contact pad options:
 - steel-sprayed
 - rubber faced
 - polyurethane faced
 - full length contact pads.

